FIG. 1A

Application Server
126

100

Universal Queuing System 102

Web Server 146

EAI Object Manager 190

UQ Business Service 106

Communication Server 109

Inbound Communication Receiver 170

Web Server 188

Object Manager 107

Request Mode Communication Server 140

Channel Driver 120B

Session Mode Communication Server 110

Workflow Process 144

Channel Driver 120A

Channel Driver 120C

120

130

Communication API 125

Communication Channel 130A

Communication Channel 130B

Communication Channel 130C

Communication Channel 130D

Customer

Customer

Customer

Customer

104

Java applet 116

Toolbar 105

Web Browser Client 104A

Agent

FIG. 1B

Request Mode Communication Server 140

Request →

Server Thread 142

Communication Manager
152

Communication Channel
Manager
156

Communication
API 125

Email Driver 120E

Email Server 132

Email Client 134

Email Communication Channel 130F

FIG. 1C

FIG. 1D

FIG. 1E

100

Application Server
126

Universal
Queuing
System 102

UQ Business
Service
106

Web Server
146

EAI Object
Manager 190

Web Server
188

Object
Manager
107

Communication Server 109

Inbound
Communication
Receiver
170

Request Mode
Communication
Server
140

Session Mode
Communication
Server
110

Workflow
Process
144

Channel
Driver
120C

Channel
Driver
120B

Channel
Driver
120A

120

130

Communication
Channel 130D

Communication
Channel 130C

Communication
Channel 130B

Communication
Channel 130A

Customer

Customer

Customer

Customer

Customer

Communication
API 125

104

Java applet
116

Toolbar 105

Web Browser
Client
104A

Thin Client
104B

Toolbar 105

Dedicated
Client
104C

Web Server
149

Object
Manager 151

Toolbar 105

Agent

Agent

Agent

FIG. 1F

FIG. 1G

Communication Server 109

Client Object 179A	Client Object 179B	Client Object 179C

Channel Driver 120

Driver Object 189

Service Object 183A	Service Object 183B	Service Object 183C

FIG. 1H

FIG. 1I

Driver Object 189

User 1 (ext.1234)
Service Object 183A

Listen
Thread

Command

Event

User 2 (ext. 5678)
Service Object 183B

Listen
Thread

Command

Event

FIG. 1K

Driver Object 189

Listen Thread

Event

Service Object
183A

Service Object
183B

Command

Command

FIG. 1J

FIG. 2

FIG. 2a: CNCTR, Communication Channel Driver Table

Column Name	Type	Length	Comments
CNCTR_ID	Varchar	15	Identifier for channel driver channel driver CNCTR. CNCTR refers to software *connector*.
NAME	Varchar	75	Name of channel driver.
MEDIA_TYPE	Varchar	50	Media type. The value of this column can be expanded by customer.
LIB_NAME	Varchar	250	File name of channel driver DLL
INBOUND_FLG	Char	1	To indicate whether this channel driver supports inbound communications
OUTBOUND_FLG	Char	1	To indicate whether this channel driver supports outbound communications
CNCTR_MEDIA_STR	Varchar	100	The media string defined by the driver vendor, which will be used at run time to invoke the media service for the channel driver.
DESC_TEXT	Varchar	250	Comments
UQ_DRIVER_FLAG	Char	1	To indicate whether this channel driver is Universal Queuing type of channel driver

FIG. 2b: CNCTR_PARM, Channel Driver Parameter Table

Column Name	Type	Length	Comments
CNCTR_PARM_ID	Varchar	15	Identifier for channel driver parameter
NAME	Varchar	75	Name of channel driver parameter
DFLT_VALUE	Varchar	250	Default value of channel driver parameter
CNCTR_ID	Varchar	15	
REQUIRED_FLG	Char	1	To indicate whether this parameter must have a value at runtime

FIG. 2c: PROF, Communication Channel Driver Profile Table

Column Name	Type	Length	Comments
PROF_ID	Varchar	15	Identifier for channel driver profile
NAME	Varchar	75	Name of channel driver profile
CNCTR_ID	Varchar	15	

FIG. 2d: PROF_PARM, Communication Channel Driver Profile Parameter Table

Column Name	Type	Length	Comments
PROF_PARM_ID	Varchar	15	Identifier for channel driver profile parameter
PROF_ID	Varchar	15	Channel Driver Profile ID
CNCTR_PARM_I D	Varchar	15	Parameter name ID
VALUE	Varchar	250	Override value of channel driver profile parameter.

FIG. 2e: AGENT_PREF, Agent Preference Table

Column Name	Type	Length	Comments
AGENT_PREF_ID	Varchar	15	Identifier for agent preference
EMP_ID	Varchar	15	
SETTING_NAME	Varchar	75	Preference name
SETTING_VALUE	Varchar	250	Preference value
SETTING_TYPE	Varchar	50	Preference type, e.g., "CTI" or "Communication"

FIG. 2f: AGENT_STAT, Agent Status Table.

Column Name	Type	Length	Comments
AGENT_STAT_ID	Varchar	15	Identifier for agent status
EMP_ID	Varchar	15	Employee ID
PROF_ID	Varchar	15	The channel driver profile ID. Agent has different status for different types of channel driver profiles.
NOT_READY_FL G	Char	1	Is agent not ready?
BUSY_FLG	Char	1	Is agent busy?

FIG. 2h: TELESET, Teleset Table.

Column Name	Type	Length	Comments
TELESET_ID	Varchar	15	Identifier for teleset
NAME	Varchar	30	Teleset Name
HOSTNAME	Varchar	70	Hostname of the computer connected to the Teleset.
COMMENTS	Varchar	250	

FIG. 2i: EXTENSION, Extension Table.

Column Name	Type	Length	Comments
EXTENSION_ID	Varchar	15	Identifier for extension
TELESET_ID	Varchar	15	Teleset ID
DN_EXT	Varchar	15	Extension Information
EXT_ACD_QUE	Varchar	30	This is the ACD queue to which this extension belongs.
EXT_TYPE	Varchar	30	ACD Extension or standard extension
AUTO_LOGIN_FLAG	Char	1	Indicate if we need to login to ACD for this extension at startup.

FIG. 2j: AGENT, Communication Agent Table.

Column Name	Type	Length	Comments
AGENT_ID	Varchar	15	Identifier for agent
PR_CFG_ID	Varchar	15	The primary configuration the agent uses.
EMP_ID	Varchar	15	Employee ID
ACTIVE_CFG_ID	Varchar	15	The currently active configuration.
ACTIVE_TELESET_ID	Varchar	15	The Teleset that the agent is currently using.

FIG. 2k: AGENT_TELSET, Communication Agent-Teleset Table

Column Name	Type	Length	Comments
AGENT_TELSET_ID	Varchar	15	Identifier for agent/teleset relationship
AGENT_ID	Varchar	15	Agent ID
TELESET_ID	Varchar	15	Teleset ID

FIG. 2l: AGENT_QUE, Agent-Queue Table.

Column Name	Type	Length	Comments
AGENT_QUE_ID	Varchar	15	Identifier for agent/queue relationship
AGENT_ID	Varchar	15	Agent ID
ACD_QUEUE_NAME	Varchar	30	ACD Queue
AUTO_LOGIN_FLAG	Char	1	Indicates need to login to ACD for this extension at startup.

FIG. 2m: AGENT_LIM, Communication Agent Limitation Table.

Column Name	Type	Length	Comments
AGENT_LIM_ID	Varchar	15	Identifier for agent limitation
AGENT_ID	Varchar	15	Agent ID
PROF_ID	Varchar	15	Channel Driver Profile ID that agent cannot use.

FIG. 2n: CFG, Communication Configuration Table.

Column Name	Type	Length	Comments
CFG_ID	Varchar	15	Identifier for configuration
NAME	Varchar	30	Configuration name
INGRP_FLAG	Char	1	To indicate whether this configuration is for inbound response group used in inbound communication receiver.
COMMENTS	Varchar	250	

FIG. 2o: CFG_PROF, Communication Configuration Channel Driver Profile Table

Column Name	Type	Length	Comments
CFG_PROF_ID	Varchar	15	Configuration/channel driver profile relationship
CFG_ID	Varchar	15	Configuration ID
PROF_ID	Varchar	15	Channel Driver Profile ID

FIG. 2p: AGENT_CFG, Communication Agent - Configuration Table

Column Name	Type	Length	Comments
AGENT_CFG_ID	Varchar	15	Identifier for agent/configuration relationship
AGENT_ID	Varchar	15	Agent ID
CFG_ID	Varchar	15	Configuration ID

FIG. 2q: CFG_PARM, Communication Configuration Parameter Table.

Column Name	Type	Length	Comments
CFG_PARM_ID	Varchar	15	Identifier for configuration parameterand
CFG_ID	Varchar	15	Configuration ID
NAME	Varchar	50	Parameter Name
VALUE	Varchar	50	Parameter Value
ACTIVE_FLG	Char	1	Active flag is set if the value is valid

FIG. 2r: CMD, Communication Command Table

Column Name	Type	Length	Comments
CMD_ID	Varchar	15	Identifier for command
CFG_ID	Varchar	15	Configuration ID
NAME	Varchar	70	Command name
TYPE	Varchar	50	Command type
PROF_ID	Varchar	15	The channel driver profile ID for the channel driver profile that this command is targeting.

FIG. 2s: CMD_PARM, Communication Command Parameter Table

Column Name	Type	Length	Comments
CMD_PARM_ID	Varchar	15	Identifier for command parameter
CMD_ID	Varchar	15	Command ID
PARAM_NAME	Varchar	100	Command parameter name
PARAM_VALUE	Varchar	100	Command parameter value

FIG. 2t: CMD_DATA, Communication Command Data Table

Column Name	Type	Length	Comments
CMD_DATA_ID	Varchar	15	Identifier for command data
CFG_ID	Varchar	15	Command ID
NAME	Varchar	100	Command parameter name
Comment	Varchar	200	Comment (optional)

FIG. 2u: CMD_DATA_PARAM, Communication Command Data Parameter Table

Column Name	Type	Length	Comments
CMD_DATA_PARAM_ID	Varchar	15	Identifier for command data parameter
CMD_DATA_ID	Varchar	15	Identifier for command data
PARAM_NAME	Varchar	100	Command parameter name
PARAM_VALUE	Varchar	200	

FIG. 2v: CMD_GROUP, Communication Command Group Table

Column Name	Type	Length	Comments
CMD_GROUP_ID	Varchar	15	Identifier for group of commands
SUB_CMD_ID	Varchar	15	Foreign key to command table
ORDER	Number	10	Default "0"

FIG. 2w: EVTHDLR, Communication Event Handler Table

Column Name	Type	Length	Comments
EVTHDLR_ID	Varchar	15	Identifier for event handler
PROF_ID	Varchar	15	The channel driver profile ID for the channel driver profile from which this event originated.
NAME	Varchar	100	Event name
MEDIA_EVENT	Varchar	100	Identifier for event
ORDER	Number	10	Default "0"
EVT_RESP_ID	Varchar	15	Foreign key to event response table
Comment	Varchar	200	Comment (optional)

FIG. 2x: HDLR_PARM, Communication Event Handler Parameter Table

Column Name	Type	Length	Comments
HDLR_PARM_ID	Varchar	15	Identifier for event handler response
EVT_HDLR_ID	Varchar	15	Identifier for event handler
PARAM_NAME	Varchar	100	Event parameter name
PARAM_VALUE	Varchar	200	Event parameter value

FIG. 2y: EVTRESP, Communication Event Response Table

Column Name	Type	Length	Comments
EVTRESP_ID	Varchar	15	Identifier for event response
CFG_ID	Varchar	15	Identifier for configuration
NAME	Varchar	100	Event parameter name
COMMENT	Varchar	200	Comment (optional)

FIG. 2z: EVTRESP_PARM, Communication Event Response Parameter Table

Column Name	Type	Length	Comments
RESP_PARM_ID	Varchar	15	Identifier for event response parameter
EVTRESP_ID	Varchar	15	Identifier for event response
PARAM_NAME	Varchar	100	Event response parameter name
PARAM_VALUE	Varchar	200	Event response parameter value

FIG. 2aa: EVTLOG, Communication Event Log Table

Column Name	Type	Length	Comments
EVTLOG_ID	Varchar	15	Identifier for event log
CFG_ID	Varchar	15	Foreign key for configuration table
NAME	Varchar	100	Event parameter name
COMMENT	Varchar	200	Comment (optional)

FIG. 2bb: LOG_PARM, Communication Event Log Parameter Table

Column Name	Type	Length	Comments
LOG_PARM_ID	Varchar	15	Identifier for event log parameter
EVTLOG_ID	Varchar	15	Identifier for event log
PARAM_NAME	Varchar	100	Event log parameter name
PARAM_VALUE	Varchar	200	Event log parameter value

FIG. 2cc: EVTRESP_LOG Event Response – Event Log Table

| Column Name	Type	Length	Comments
RESP_LOG_ID	Varchar	15	Identifier for response log
EVTRESP_ID	Varchar	15	Identifier for event response
EVTLOG_ID	Varchar	15	Identifier for event log
LOG_TYPE	Varchar	100	Type of EventLog declaration specified in EventResponse definition.

FIG. 3

FIG. 4A: TABLE UQ_CFG

Column_Name	Type	Length	Comments
NAME	Varchar	75	
SERVER_NAME	Varchar	75	
SERVER_PORT	Number	10	
RECEIVER_NAME	Varchar	75	
RECEIVER_PORT	Number	10	

FIG. 4B: TABLE UQ_CFG_PARAM

Column_Name	Type	Length	Comments
UQ_CFG_ID	Varchar	15	
NAME	Varchar	50	
VALUE	Varchar	50	

FIG. 4C: TABLE UQ_ROUTE

Column_Name	Type	Length	Comments
NAME	VarChar	75	User defined name of the route
MEDIA_TYPE_CD	VarChar	30	Select from value of list. Possible values include "PBX", "Web Chat", "Web Collaboration", "Fax", "E-Mail"
ACTIVE_FLG	Char	1	Indicates wheter this route is active or not. If the route is not active, information for this route will not be passed to UQ engine.
PRIORITY_CD	Varchar	30	Lower the value higher the priority.
CAPACITY	Number	10	Maximum capacity of this route. Alarm should be generated when the number of queued item exceeds the CAPACITY
TIME_OUT_SCND	Number	10	Time in second in which when the work item is not server, the first escalation rule will be effective.

FIG. 4D: TABLE UQ_ROUTE_PROP

Column_Name	Type	Length	Comments
UQ_ROUTE_ID	Varchar	15	
NAME	Varchar	75	Name of the property
VALUE	Varchar	75	Value of the property

FIG. 4E: TABLE UQ_ROUTE_ESCL

Column_Name	Type	Length	Comments
UQ_ROUTE_ID	Varchar	15	
NAME	Varchar	75	Name of the escalation rules
TIME_OUT_SCND	Number	10	Time in seconds in which the escalation rule will be timed out. Zero time means waiting indefinitely.
SEQ_NUM	Number	10	Order of escalation rules

FIG. 4F: TABLE UQ_RTESCL_RUL

Column_Name	Type	Length	Comments
ROUTE_ESCL_ID	Varchar	15	
SKILL_NAME	Varchar	50	Skill
SKILL_ITEM	Varchar	50	If skill item is null, it is a substitution of language from the work item data property.
EXPERTISE	Varchar	30	LOV, default Value

FIG. 4G: TABLE UQ_SKL_MAP

Column_Name	Type	Length	Comments
ROUTE_PROP_NAME	Varchar	75	
ROUTE_PROP_VALUE	Varchar	75	
SKILL_NAME	Varchar	75	
SKILL_VALUE	Varchar	75	

FIG. 4H: TABLE UQ_USER_MEDIA

Column Name	Type	Length	Comments
USER_ID	Varchar	15	
MEDIA_TYPE_CD	varchar	30	
MAX_NUM_SESSIONS	Number	10	Maximum session allowed.

FIG. 4I: TABLE UQ_ROUTE_STS

Column_Name	Type	Length	Comments
ROUTE_ID	Varchar	75	
START_TS	Date Time		
END_TS	Date Time		
SOURCE_NAME	Varchar	75	Either the route name
AVG_WAIT_TM	Number	10	Waiting time during the given period
AVG_HANDLE_TM	Number	10	Handling time during the period
NUM_ABANDONED_REQS	Number	10	Number of abandon request
AVG_ABANDONING_TM	Number	10	
LONGEST_WAIT_TM	Number	10	Longest waiting time in seconds
AVAIL_USER_PCT	Number	10	Percentage of available agents
AUX_WORK_USER_PCT	Number	10	Percentage of auxwork agents
TOTAL_NUM_WORKITEMS	Number	10	Total number of agent if each agent handle only one work item
TOTAL_NUM_UNASSIGNED_WORKITEM	Number		
TOTAL_NUM_DELIVERED_WORKITEM	Number		
TOTAL_NUM_SERVICE_LEVEL_WORKITEM	Number		
Comments	Varchar	250	

FIG. 4J: TABLE UQ_MEDIA_STS

Column_Name	Type	Length	Comments
MEDIA_TYPE_CD	Varchar	30	
START_TS	Date Time		
END_TS	Date Time		
SOURCE_NAME	Varchar	75	Either the route name
AVG_WAIT_TM	Number	10	Waiting time during the given period
AVG_HANDLE_TM	Number	10	Handling time during the period
NUM_ABANDONED_REQS	Number	10	Number of abandon request
AVG_ABANDONING_TM	Number	10	
LONGEST_WAIT_TM	Number	10	Longest waiting time in seconds
AVAIL_AGENT_PCT	Number	10	Percentage of available agents
AUX_WORK_AGENT_PCT	Number	10	Percentage of auxwork agents
TOTAL_NUM_WORKITEMS	Number	10	Total number of agent if each agent handle only one work item
TOTAL_NUM_UNASSIGNED_WO RKITEM	Number		
TOTAL_NUM_DELIVERED_WOR KITEM	Number		
TOTAL_NUM_SERVICE_LEVEL_ WORKITEM	Number		
Comments	Varchar	250	

FIG. 4K: TABLE UQ_AGENT_STS

Column_Name	Type	Length	Comments
AGENT_ID	Varchar	15	
START_TS	Date Time	7	
END_TS	Date Time	7	
CONTACT_ID	Varchar	15	
AVAIL_PCT	Number		Percentage available
BUSY_PCT	Number		Percentage busy
AUX_WORK_PCT	Number		Percentage auxwork
NUM_COMM_ITEM_SRVD	Number		Number of work item served
Comments	Varchar	250	

FIG. 4L: TABLE UQ_ERR_LOG

Column_Name	Type	Length	Comments
Name	DateTime	7	
TYPE_CD	Varchar	30	Either alarm or error
Severity	Varchar	30	
ERROR_CODE	Varchar	10	Alarm code or error code
MSG_DESC	Varchar	250	Template for message

FIG. 4M: **S_JOURNAL**

| Column_Name	Type	Length	Comments
WORK_ITEM_ID	Varchar	250	Work item ID
ROUTE_NAME	Varchar	75	The name of the route. Use the actual name instead of ID because the nature of the route could be changing from time to time.

Fig. 4n: S_JOURNAL_WORKITEM_PROPERTY

Column_Name	Type	Length	Comments
JOURNAL_ID	Varchar	15	
Name	Varchar	75	Name of the property
Value	Varchar	75	Value of the property

Fig. 4o: S_JOURNAL_ESC_HIST

Column_Name	Type	Length	Comments
JOURNAL_ID	Varchar	15	
ESC_STEP_NAME	Varchar	75	
START_TIME	Date Time		Start time
END_TIME	Date Time		
RESULT	Varchar	75	

Fig. 4p: S_JOURNAL_STATE_HIST

Column_Name	Type	Length	Comments
JOURNAL_ID	Varchar	15	
USERID	Varchar	15	
START_TIME	Date Time		Start time
END_TIME	Date Time		
AGENTSTATE	Varchar	50	
REASON	Varchar	50	

FIG. 5

Computer System 10

- Central Processor 14
- Bus 12
- System Memory 16
- I/O Controller 18
- Network Interface 48
- Floppy Disk Unit 36
- Floppy Disk 38
- Modem 47
- Serial Port 30
- Audio Interface 22
- Speaker System 20
- CD-ROM Player 40
- CD-ROM 42
- Storage Interface 34
- Fixed Disk 44
- Keyboard Controller 33
- Keyboard 32
- Serial Port 28
- Mouse 46
- Display Adapter 26
- Display Screen 24

FIG. 6

FIG. 7